



PART NO.	CONDUCTOR MATERIAL	CURRENT WITH PLUG	CURRENT WITHOUT PLUG
FA14935	COPPER	26 AMPS	55 AMPS
FA14935-02	MOLYBDENUM	26 AMPS	28 AMPS
FA14935-03	NICKEL	16.5 AMPS	16.5 AMPS
FA14935-04	304 STN STL	3.6 AMPS	3.6 AMPS

	RATINGS	
	WITH PLUG	WITHOUT PLUG
VOLTAGE:	10KV DC	5KV DC
CURRENT:	SEE TABLE AT LEFT	SEE TABLE AT LEFT
TEMPERATURE:	-25°C TO 125°C	-25° TO 205°C

MATES WITH POWERPLUG FP10884-02

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.				THIRD ANGLE PROJECTION 			TITLE: TWELVE 10KV FEEDTHROUGHS		
REV. APP'D DATE SCALE 7:8 DIMENSIONS IN INCHES [mm]	DRAWN MH 08/29/2006	PART NO. (SEE TABLE) REV. A		SALES DWG NO. FA14935SL REV. A1					
A1 MH 08/29/2006 FTST0027-1ST	ENG APPR. MH 08/29/2006								