

PART NO.	CONDUCTOR MATERIAL	T/C TYPE
FA11684	PLATINUM / RHODIUM*	R/S
FA11684-02	COPPER / CONSTANTAN	T


*TYPE R/S USES COMPENSATING WIRE
 MAXIMUM JUNCTION TEMPERATURE 250°C

RATINGS	
CONDUCTOR MATERIAL:	SEE TABLE AT LEFT
T/C TYPE:	SEE TABLE AT LEFT
TEMPERATURE:	-269°C TO 450°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE: TWO PAIR T/C LOOP TYPE
 FEEDTHROUGH



SOLID SEALING TECHNOLOGY, INC.

REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	JM	1/12/2006
B1	MH	05/26/2006	MPCL0030-ST		ENG APPR.	MH	05/26/2006

PART NO. (SEE TABLE) REV. B

SALES DWG NO. FA11684SL REV. B1