

PART No	T/C TYPE	CONDUCTOR MATERIAL
FA14918	R/S	PLATINUM / RHODIUM*
FA14918-02	T	COPPER / CONSTANTAN


RATINGS	
TEMPERATURE:	-269° TO 450°C

*TYPE R/S USES COMPENSATING WIRE
 MAXIMUM JUNCTION TEMPRATURE 250°C

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLID SEALING TECHNOLOGY. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLID SEALING TECHNOLOGY IS PROHIBITED.

THIRD ANGLE PROJECTION



TITLE: ONE PAIR T/C LOOP STYLE FEEDTHROUGH



REV.	APP'D	DATE	SCALE 1:1	DIMENSIONS IN INCHES [mm]	DRAWN	MH	09/01/2006
A1	MH	09/01/2006	MPLC0027-2ST		ENG APPR.	MH	09/01/2006

PART NO. (SEE TABLE) REV. A

SOLID SEALING TECHNOLOGY, INC.

SALES DWG NO. FA14918SL REV. A1